

CASES
1460
Case



1460 Case



- **Top lid opens up to 180° for on-the-field anti-roll stability when open**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Comfortable rubber over-molded handles
- Stainless steel hardware and padlock protectors
- Pick N Pluck™ with convoluted lid foam
- Personalized nameplate service available
- Lifetime Guarantee of Excellence
- Also available with EMS Organizer and Dividers
- **Watertight, crushproof, and dust proof**

1460 Case Configurations

Cat. #	Description
1460	1460 Case
1460NF	1460 Case (No foam)
1460AALG	1460 Case (with custom foam for 9430/9435)



Black



OD Green*



Desert Tan

*OD Green available upon request

1460 Case Specifications

Exterior Dimensions (L x W x D)	Interior Dimensions (L x W x D)	
20.85" x 12.73" x 12.75" (52.9 x 32.3 x 32.4 cm)	18.54" x 9.92" x 10.92" (47.1 x 25.2 x 27.7 cm)	
Lid Depth	Bottom Depth	Total Depth
4.91" (12.5 cm)	6.01" (15.3 cm)	10.92" (27.7 cm)
Weight with foam	Weight without foam	Buoyancy Max.
12.48lbs. (5.66 kg)	8.75 lbs. (3.97 kg)	82 lbs. (37.19 kg)

Range Temperature

-40 / 210° F (-40 / 99° C)

1460 Case Certificates

- IP67 (1 meter submersion for 30 minutes)

1460 Case Accessories

Cat. #	Description
1461	Replacement Foam Set
1463	Replacement O-ring