

CASES
iM2100
 Pelican Storm Case



iM2100 Storm Case



- Two Press & Pull Latches
- Double-layered, Soft-grip Handle
- Two Padlockable Hasps
- Vortex® Valve
- Flush Powerful Hinges
- Meets Carry-on Regulations
- Lightweight Strong HPX® Resin
- Watertight
- Guaranteed For Life

iM2100 Storm Case Configurations

Cat. #	Description
iM2100	iM2100 Storm Case
iM2100-X0000	iM2100 Storm Case (No foam)
iM2100-X0002	iM2100 Storm Case with Padded Dividers



Black



Yellow



OD Green

iM2100 Storm Case Specifications

Exterior Dimensions (L x W x D)	Interior Dimensions (L x W x D)	
14.20" x 11.40" x 6.50" (36.1 x 28.9 x 16.5 cm)	13.00" x 9.20" x 6.00" (33 x 23.4 x 15.2 cm)	
Lid Depth	Bottom Depth	Total Depth
2.00" (5.1 cm)	4.00" (10.2 cm)	6.00" (15.2 cm)
Weight with foam	Weight without foam	Buoyancy Max.
4.9 lbs. (2.22 kg)	4.2 lbs. (1.91 kg)	33.82 lbs. (15.34 kg)
Range Temperature		
-20 / 140° F (-29 / 60° C)		

iM2100 Storm Case Certificates

• MIL-STD-810F • FED-STD-101C • ATA 300

iM2100 Storm Case Accessories

Cat. #	Description
iM-LIDSTAY	Lid Stay
iM-STRAP-S-VER2	Padded Shoulder Strap
iM-VALVE-M-B	Manual Purge Valve
iM2100-BEZEL	Base Bezel Kit
iM2100-DIV	Padded Dividers
iM2100-FOAM	Replacement Foam