



iM2500 Storm Carry On Case



- Two Press & Pull Latches
- Double-layered, Soft-grip Handle
- Two Padlockable Hasps
- In-line Wheels
- Telescoping Handle
- Vortex® Valve
- Flush Powerful Hinges
- Meets Carry-on Regulations
- Lightweight Strong HPX® Resin
- Watertight
- Guaranteed For Life

iM2500 Storm Carry On Case Configurations

Cat. #	Description
iM2500	iM2500 Storm Carry On Case
iM2500-X0000	iM2500 Storm Case (No foam)
iM2500-X0002	iM2500 Storm Case with Padded Dividers



Black



Yellow



OD Green

iM2500 Storm Carry On Case Specifications

Exterior Dimensions (L x W x D)	Interior Dimensions (L x W x D)	
21.70" x 14.10" x 8.90" (55.1 x 35.8 x 22.6 cm)	20.50" x 11.50" x 7.20" (52 x 29.2 x 18.3 cm)	
Lid Depth	Bottom Depth	Total Depth
2.00" (5.1 cm)	5.20" (13.2 cm)	7.20" (18.3 cm)
Weight with foam	Weight without foam	Buoyancy Max.
13.7 lbs. (6.21 kg)	11.1 lbs. (5.03 kg)	87.39 lbs. (39.64 kg)
Range Temperature	No. of Wheels	Retractable Handle
-20 / 140° F (-29 / 60° C)	2	YES

iM2500 Storm Carry On Case Certificates

• MIL-STD-810F • FED-STD-101C • ATA 300

iM2500 Storm Carry On Case Accessories

Cat. #	Description
iM-LIDSTAY	Lid Stay
iM-STRAP-S-VER2	Padded Shoulder Strap
iM-VALVE-M-B	Manual Purge Valve
iM2500-BEZEL	Base Bezel Kit
iM2500-BEZEL-LID	Lid Bezel Kit
iM2500-DIV	Padded Dividers
iM2500-FOAM	Replacement Foam
iM2500-UTILITYORG	Utility Organizer